UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/800,848	03/16/2004	David K. Biegelsen	117364	1293
65575 OLIFF & BERI	7590 07/23/200 RIDGE. PLC	EXAMINER		
P.O. BOX 3208	350	OLANIRAN, FATIMAT O		
ALEXANDRIA, VA 22320-4850			ART UNIT	PAPER NUMBER
			2614	
			MAIL DATE	DELIVERY MODE
			07/23/2009	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)	
	10/800,848	BIEGELSEN, DAVID K.	
Office Action Summary	Examiner	Art Unit	
	FATIMAT O. OLANIRAN	2614	
The MAILING DATE of this communication app Period for Reply	pears on the cover sheet with the c	correspondence address	
A SHORTENED STATUTORY PERIOD FOR REPL WHICHEVER IS LONGER, FROM THE MAILING D - Extensions of time may be available under the provisions of 37 CFR 1.1 after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period - Failure to reply within the set or extended period for reply will, by statute Any reply received by the Office later than three months after the mailin earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 136(a). In no event, however, may a reply be tinwill apply and will expire SIX (6) MONTHS from e, cause the application to become ABANDONE	N. nely filed the mailing date of this communication. D (35 U.S.C. § 133).	
Status			
1) ☐ Responsive to communication(s) filed on 15 J 2a) ☐ This action is FINAL . 2b) ☐ This 3) ☐ Since this application is in condition for alloware closed in accordance with the practice under B	s action is non-final. ince except for formal matters, pro		
Disposition of Claims			
4) ☐ Claim(s) 1.3-6.8-11 and 13-23 is/are pending 4a) Of the above claim(s) is/are withdra 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) 1.3-6.8-11 and 13-23 is/are rejected. 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and/or	wn from consideration.		
Application Papers			
9) The specification is objected to by the Examine 10) The drawing(s) filed on is/are: a) accomposed applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the Examine 11.	cepted or b) objected to by the liderawing(s) be held in abeyance. Section is required if the drawing(s) is objected.	e 37 CFR 1.85(a). jected to. See 37 CFR 1.121(d).	
Priority under 35 U.S.C. § 119			
12) ☐ Acknowledgment is made of a claim for foreign a) ☐ All b) ☐ Some * c) ☐ None of: 1. ☐ Certified copies of the priority document 2. ☐ Certified copies of the priority document 3. ☐ Copies of the certified copies of the priority application from the International Burea * See the attached detailed Office action for a list	ts have been received. ts have been received in Applicati ority documents have been receive u (PCT Rule 17.2(a)).	on No ed in this National Stage	
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date	4) Interview Summary Paper No(s)/Mail Da 5) Notice of Informal F 6) Other:	ate	

Application/Control Number: 10/800,848 Page 2

Art Unit: 2614

DETAILED ACTION

Response to Remarks

1. Applicant's remarks filed 6/15/2009 with regards to the interview of 6/2/2009 have been considered. Examiner suggested in the interview of 6/2/2009 claiming the same transmitting and receiving array in order to distinguish applicant's claim from the cited art. In addition applicant's amendment of a "plurality of objects" does not overcome the cited art because applicant does not claim a simultaneous detection of a plurality of objects. Pompei in view of Kino may detect various objects one after the other or in succession (Kino; col. 2 line 5-15) and therefore read on a plurality of objects.

Claim Rejections - 35 USC § 103

- 1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 2. Claim 1, 3-6, 8-11, 13-23 are rejected under 35 U.S.C. 103(a) as being unpatentable over Pompei (2001/0007591) in view of Kino et al (3953825) in further view of Manabe (6556687).

Pompei discloses a method for processing hypersonic signals performed by a hypersonic signal-emitting device (Fig. 1 and paragraph 39) comprising parameters for

optimal focus on said objects (paragraph 39 and paragraph 54); and transmitting audio information based on the parameters to the plurality of objects detected at locations corresponding to the neighborhoods based on the parameters (paragraph 21 and paragraph 54).

Pompei does not explicitly discloses generating a signal; and forming a plurality of individual transducer outputs of the signal at a plurality of phases, the outputs having a common frequency and amplitude the individual transducer outputs generating wavelets originating at a common origin with reference to a first axis, and the plurality of phases being generated using electronic delays; forming one or more focused hypersonic beams based on the wavelets receiving one or more reflected hypersonic signals; detecting objects based on the reflected hypersonic signals; learning sets of transmission parameters for optimal focus on said objects, the learning including associating sets of transmission parameters with detected objects, storing the sets of transmission parameters and computing a resultant set of transmission parameters based ion the stored sets of transmission parameters; generating the plurality of hypersonic wavelets based on the resultant set of transmission parameters associated with one or more neighborhoods for the hypersonic beams.

However Pompei suggests a ranging system incorporated in the audio unit (paragraph 54).

Kino discloses a method for processing hypersonic signals performed by a hypersonic signal-emitting device (Fig. 1 and col. 3 lines 38-55), comprising; generating a signal

(Fig. 1 and col. 3 line 45-46); and forming a plurality of individual transducer outputs of the signal at a plurality of phases, the outputs having a common frequency and amplitude the individual transducer outputs generating wavelets originating at a common origin with reference to a first axis, and the plurality of phases being generated using electronic delays; forming a plurality of focused hypersonic beams based on the wavelets (Fig.1-3)

receiving a plurality of reflected hypersonic signals; detecting an object based on the plurality reflected hypersonic signals (Fig.1-3 and col. 3 line 35-40, col. 2 line 5-15); learning sets of transmission parameters for optimal focus on an object objects (Fig.1-3 and col. 5 line 50-68 and col. 6 line 1-37), the learning including associating a set of transmission parameters detected objects (Fig.1-3 and col. 6 line 1-50), storing the sets of transmission parameters (inherent) and computing a resultant set of transmission parameters (col. 6 line 1-37 and col. 9 line 1-12) based on the stored sets of transmission parameters; generating the plurality of hypersonic wavelets based on the resultant set of transmission parameters associated with a neighborhood for the hypersonic beams (Fig. 1-3 and col. 6 line 1-37).

Therefore it would have been obvious to one of ordinary skill in the art at the time of the invention to modify the parametric audio system of Pompei with the imaging method of Kino in order to determine the location of the nearest listener and send an audio message (Pompei paragraph 54).

Kino does not explicitly disclose plurality of neighborhoods and plurality of objects, However Kino discloses various types of object (col. 2 line 5-15). It would have been

obvious to one of ordinary skill in the art at the time of the invention that the imager of Kino can be used repeatedly in different environments (col. 2 line 5-15). In addition Pompei discloses audio signal regeneration along paths of projection (par 21).

Therefore it would have been obvious to one of ordinary skill in the art at the time of the invention to modify the parametric audio system of Pompei with the imaging method of Kino in order to determine the location of a plurality of objects and send an audio message (Pompei paragraph 54).

In addition Manabe teaches using a hypersonic signal emitting device to determine the distance of a listener and to send audio messages to the listener (col. 9 line 1-22). Therefore it would have been obvious to one of ordinary skill in the art at the time of the invention to modify the parametric audio system of Pompei with the imaging method of Kino in order to have a compact system that can provide audio to a select user.

Claim 3 analyzed with respect to claim 1, Pompei in view of Kino disclose synthesizing one or more hypersonic ping signals; and emitting the hypersonic ping signals as the focused hypersonic beams (Kino; Fig. 1 and col. 3 line 45-64).

Claim 4 analyzed with respect to claim 1 and 3, Pompei in view of Kino discloses encoding the hypersonic ping signals using one or more frequencies; and directing each of the focused hypersonic beams in different directions, each of the focused hypersonic beams corresponding to one of the hypersonic ping signals (Kino; Fig. 1 and col. 6 lines 25-37)

Claim 5 analyzed with respect to claim 1, Pompei in view of Kino discloses further comprising: setting a coordinate system for a space; scanning the space based on the coordinate system (a coordinate system is inherent to a space); and recording object parameters corresponding to detected objects (Kino; Fig. 1 and col. 6 lines 25-37 and col. 9 line 1-12)

Claim 6 analyzed with respect to claim 1 and 5, Pompei in view of Kino discloses disclose the coordinate system is suitable for one, two or three dimensional space (inherent and Kino; col. 2 line 60-68).

Claim 8 analyzed with respect to claim 1 and 5-6, Pompei in view of Kino discloses selecting one or more carrier hypersonic frequencies based on the parameters; generating one or more side bands, one side band corresponding to each of the carrier hypersonic frequencies, the side bands being encoded with audio information (Pompei; paragraph 8 line 4-12); generating a plurality of output signals, each of the output signals corresponding to one of the side bands; generating a plurality of sets of phase shifts; generating a plurality of driving signals, each of the driving signals being a combination of the plurality of output signals, wherein each of the output signals is phase shifted by an appropriate phase shift of the set of phase shifts for that output signal; and driving each of the hypersonic wavelets with one of the driving signals (Pompei; paragraph 8 line 32-46).

Claim 9 analyzed with respect to claim 1 and 5-6, Pompei in view of Kino discloses further comprising: receiving environment information; and setting the parameters based on the environment information (Pompei, paragraph 54, line 5-11).

Claims 10, Pompei in view of Kino discloses disclose a computer readable medium or a modulated signal being encoded to perform the method of claim 1 (Pompei, paragraph 40, line 12-16).

Claim 11, Pompei discloses a memory (inherent and Fig. 1) a plurality of transducer elements formed into a transducer element array (Fig. 1) and parameters for optimal focus on said objects and a signal generator that generates an output signal to encode audio information for transmission to a chosen location based on the learned parameters (Fig. 1 and paragraph 21 and paragraph 54).

Pompei does not explicitly disclose the transducer elements all having a common position with reference to a first axis; a driver that drives the transducer elements with a signal at a plurality of phases, the driver having a delay processor that forms the phases of the signal causing the transducer element array to form a focused hypersonic beam; a detector that detects objects based on echo signals received by the transducer element array; a device that learns sets of transmission parameters for optimal focus on said objects, the learning including associating sets of transmission parameters with

detected objects, storing the sets of transmission parameters in a memory and computing resultant set of transmission parameters based on the stored sets of transmission parameters;

However Pompei suggests a ranging system incorporated in the audio unit (paragraph 54).

Kino discloses a plurality of transducer elements formed into a transducer element array the transducer elements all having a common position with reference to a first axis; a driver that drives the transducer elements with a signal at a plurality of phases, the driver having a delay processor that forms the phases of the signal causing the transducer element array to form a focused hypersonic beam (Fig. 1 and col. 6 line 25-37); a detector that detects objects based on echo signals received by the transducer element array (Fig. 1 and col. 6 line 1-50 and col. 9 line 5-13); a device that learns sets of transmission parameters for optimal focus on said objects (Fig.1-3 and col. 5 line 50-68 and col. 6 line 1-37), the learning including associating a set of transmission parameters with detected objects (Fig.1-3 and col. 6 line 1-50 and col. 9 line 5-13), storing the sets of transmission parameters in a memory (some form of memory inherent to invention) and computing resultant set of transmission parameters (col. 6 line 1-37 and col. 9 line 1-12) based on the stored sets of transmission parameters; Therefore it would have been obvious to one of ordinary skill in the art at the time of the invention to modify the parametric audio system of Pompei with the imaging method of Kino in order to determine the location and of the nearest listener and send an audio message (Pompei paragraph 54).

Kino does not explicitly disclose plurality of neighborhoods and plurality of objects,

However Kino discloses various types of object (col. 2 line 5-15). It would have been
obvious to one of ordinary skill in the art at the time of the invention that the imager of
Kino can be used repeatedly in different environments (col. 2 line 5-15). In addition
Pompei discloses audio signal regeneration along paths of projection (par 21).

Therefore it would have been obvious to one of ordinary skill in the art at the time of the
invention to modify the parametric audio system of Pompei with the imaging method of
Kino in order to determine the location of a plurality of objects and send an audio
message (Pompei paragraph 54).

In addition Manabe teaches using a hypersonic signal emitting device to determine the distance of a listener and to send audio messages to the listener (col. 9 lines 1-22). Therefore it would have been obvious to one of ordinary skill in the art at the time of the invention to modify the parametric audio system of Pompei with the imaging method of Kino in order to have a compact system that can provide audio to a select user.

Claim 13 analyzed with respect to claim 11, Pompei in view of Kino disclose the signal generator comprising: a frequency selector that selects one or more frequencies based on transmission parameters (Pompei, paragraph 22, line 7-9, acoustic transducers); a delay processor that determines a plurality of delays corresponding to the hypersonic transducer elements that is required to form a focused hypersonic beam directed at a specified direction (Pompei, paragraph 23, line 9-14); and a signal generator that

generates a signal that includes selected frequencies, the signal being delayed by a corresponding one of the plurality of delays before driving each of the hypersonic transducer elements through the driver (Pompei, Fig. 4 and paragraph 34, line 1-10).

Claim 14 analyzed with respect to claim 11 and 13, Pompei in view of Kino disclose the frequency selector selecting the frequencies based on a noise environment (inherent to the operation of a transducer) the frequencies being selected to form a code to enhance reception of echoes of the focused hypersonic beam from the objects (Kino; col. 4 line 35-48).

Claim 15, analyzed with respect to claim 11, Pompei in view of Kino disclose further comprising a controller that sets a coordinate system for a space, scans the space by directing the focused hypersonic beam to proceed based on the coordinate system, and records coordinates of detected objects based on echoes from the focused hypersonic beam (Kino, abstract and Fig. 1 and col. 4 line 35-48 and col. 6 line 25-48).

Claim 16 analyzed with respect to claim 11 and 15, Pompei in view of Kino disclose further comprising a signal generator that generates an output signal corresponding to each of the hypersonic transducer elements based on parameters stored in the memory, the controller specifying a neighborhood for the focused hypersonic beam based on one or more object locations and controlling the signal generator to generate the output signal to encode audio information for transmission to the neighborhood (Pompei, paragraph 54, line 3-11 and paragraph 21, line 1-4).

Claim 17 analyzed with respect to claim 11, 15-16, Pompei in view of Kino disclose the signal generator generating the output signal to include a side band for encoding the audio information(Pompei; paragraph 8 line 4-12); the delay processor generating a set of driving signals, each of the driving signals being the output signal delayed by one of a set of delays corresponding to phase shifts for each of the transducer elements to form the focused hypersonic beam; and the driver driving one of the driving signals to each of the transducer elements to form the focused hypersonic beam (Pompei; paragraph 8 line 32-46).

Claim 18 analyzed with respect to claims 11, 15-17, Pompei in view of Kino disclose wherein the controller selects one or more carrier frequencies for transmission of a corresponding plurality of audio information (Pompei, paragraph 22, line 21-25), the signal generator generating a plurality of output signals and the delay processor generating a plurality of sets of delays, the delay processor delaying each of the output signals by a corresponding set of delays for one of the plurality of audio information the delay processor combining all delayed output signals for each of the transducer elements and outputs combined output signal to the driver for driving each of the transducer elements (Pompei, paragraph 22, line 7-15 and paragraph 23, line 9-14).

Claim 19 analyzed with respect to claims 11, 15-18, Pompei in view of Kino disclose the hypersonic transducer transmitting a plurality of focused hypersonic beams, each of the

focused hypersonic beams delivering one of the plurality of audio information to a unique neighborhood as based on the delays (Pompei, paragraph 39, line 1-20).

Claim 20 analyzed with respect to claims 11, 15-18, Pompei in view of Kino disclose the controller receiving environment information, and selecting carrier frequencies and amplitude of the output signals based on the environment information (Pompei, paragraph 39, line 11-20).

.

Claim 21 analyzed with respect to claims 11, Pompei in view of Kino disclose means for scanning a space using a focused hypersonic beam; means for detecting the objects based on echo signals of the focused hypersonic beam (Kino Fig. 1 and abstract); and means for delivering audio information to a neighborhood of detected objects (Pompei, paragraph 8, line 4-10).

Claim 22 analyzed with respect to claims 11 and 21, Pompei in view of Kino disclose means for scanning the space using multiple focused hypersonic beams (Kino; Fig. 1 and col. 9 line 1-12); and means for delivering unique audio information to different neighborhoods using multiple hypersonic beams (Pompei paragraph 39, line 11-20).

Claim 23 analyzed with respect to claim 1, Pompei in view of Kino disclose further comprising: receiving a hypersonic signal and delaying the hypersonic signal by a

Application/Control Number: 10/800,848 Page 13

Art Unit: 2614

plurality of phases to select portions of information in the hypersonic signal (Kino; Fig. 1 and col. 6 lines 39-48 and line 63-68).

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to FATIMAT O. OLANIRAN whose telephone number is (571)270-3437. The examiner can normally be reached on M-F 10:00-6 EST.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Vivian Chin can be reached on 571-272-7848. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Application/Control Number: 10/800,848 Page 14

Art Unit: 2614

FO

/Vivian Chin/ Supervisory Patent Examiner, Art Unit 2614